

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor: : **Yassin Aden AWAD, et al.**  
Filed : **Concurrently herewith**  
For : **ADAPTIVE MODULATION AND ....**  
Serial No. : **Concurrently herewith**

July 29, 2003


Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

**PRIORITY CLAIM AND**  
**SUBMISSION OF PRIORITY DOCUMENT**

S I R:

Applicant hereby claims priority under 35 USC 119 from **British** patent application number **0217654.3** filed **July 30, 2002**, a copy of which is enclosed.

Respectfully submitted,

  
\_\_\_\_\_  
Brian S. Myers  
Reg. No. 46,947

Katten Muchin Zavis Rosenman  
575 Madison Avenue  
New York, NY 10022-2585  
(212) 940-8800  
Docket No.: FUJL 20.417





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was also filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

*P. McHoney*  
27 May 2003





# Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference	HL82706/000/PMH							
2. Patent application number <i>(if you know it)</i>	0217654.3	30 JUL 2002						
3. Full name of the or of each applicant	FUJITSU LIMITED							
4. Title of the invention	Adaptive Modulation & Coding							
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	The inventor is employed by Fujitsu Laboratories of Europe Limited (FLE) and FLE and its parent company Fujitsu Limited have agreed that this invention shall be owned by Fujitsu Limited							
6. How many, if any, additional Patents Forms 7/77 are attached to this form? <i>(see note (c))</i>	None							
7.	<p>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 40%; text-align: right;">Signature</td> <td style="width: 20%;"></td> <td style="width: 40%; text-align: right;">Date</td> </tr> <tr> <td style="text-align: right;">Haseltine Lake, Agents for the Applicants</td> <td style="text-align: center;">H. L. Lake</td> <td style="text-align: right;">30th July 2002</td> </tr> </table>		Signature		Date	Haseltine Lake, Agents for the Applicants	H. L. Lake	30th July 2002
Signature		Date						
Haseltine Lake, Agents for the Applicants	H. L. Lake	30th July 2002						
8. Name and daytime telephone number of person to contact in the United Kingdom	Mr P M Hitching	[020] 7420 0500						

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

**Patents Form 7/77**

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Yassin Aden AWAD  
29A Darwin Drive  
Southall  
Middlesex UB1 3JY

8435701 001

Patents ADP number (if you know it):

Michiharu NAKAMURA  
5 Clarendon Road  
Ealing  
London W5 1AA


8435943001

Patents ADP number (if you know it):

**Reminder**

Have you signed the form?

Patents ADP number (if you know it):



310002 5737282-1 002947  
P01-7700 0100-0217654.3

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference	HL82706/000/PMH		
2. Patent application number (The Patent Office will fill in this part)	0217654.3		30 JUL 2002
3. Full name, address and postcode of the or of each applicant (underline all surnames)	FUJITSU LIMITED 1-1, Kamikodanaka 4-chome Nakahara-ku, Kawasaki-shi Kanagawa 211-8588, Japan		
Patents ADP number (if you know it)			
If the applicant is a corporate body, give the country/state of its incorporation	Japan		
4. Title of the invention	Adaptive Modulation & Coding		
5. Name of your agent (if you have one)	Haseltine Lake		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Imperial House 15-19 Kingsway London WC2B 6UD		
Patents ADP number (if you know it)	34001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	Yes		

460154001

## Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description 24

Claim(s) 6

Abstract 1

Drawing(s) 18 118 *only*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 3

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Haseltine Lake, Agents for the Applicants

Signature *Haseltine Lake*

Date  
30th July 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr P M Hitching

[020] 7420 0500

### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*



DUPLICATE

ADAPTIVE MODULATION AND CODING

The present invention relates to adaptive modulation and coding methods and apparatus for use, for example, in wireless communication systems.

Fig. 1 shows parts of a wireless communication system 1. The system includes a plurality of base stations 2, only one of which is shown in Fig. 1. The base station 2 serves a cell in which a plurality of individual users may be located. Each user has an individual user equipment (UE). Only the user equipments UE2, UE11 and UE50 are shown in Fig. 1. Each UE is, for example, a portable terminal (handset) or portable computer.

As is well known, in a code-division multiple access (CDMA) system the signals transmitted to different UEs from the base station (also known as "node B") are distinguished by using different channelisation codes. In so-called third generation wireless communication systems a high speed downlink packet access (HSDPA) technique has been proposed for transmitting data in the downlink direction (from the base station to the UEs). In this technique a plurality of channels are available for transmitting the data. These channels have different channelisation codes. For example, there may be ten different channels C1 to C10 available for HSDPA in a given cell or sector of a cell. In HSDPA, downlink transmissions are divided up into a series of transmission time intervals (TTI) or frames, and a packet of data is transmitted on each different available channel to a selected UE. A new choice of which UE is served by which channel can be made in each TTI.

Fig. 2 shows an example of the operation of the HSDPA technique over a series of transmission time intervals TTI1 to TTI9. As shown in Fig. 2, in TTI1 it

is determined that two packets will be sent to UE50, four packets will be sent to UE11 and four packets will be sent to UE2. Accordingly, two channels are allocated to UE50 and four channels each are allocated to UE11 and UE2. Thus, as shown in Fig. 1, UE50 is allocated channels C1 and C2, UE11 is allocated channels C3 to C6, and UE2 is allocated channels C7 to C10.

In the next transmission time interval TTI2 a new user equipment UE1 is sent one packet, and the remaining UEs specified in TTI1 continue to receive packets.

Thus, effectively the HSDPA system employs a number of parallel shared channels to transmit data in packet form from the base station to the different UEs. This system is expected to be used, for example, to support world wide web (WWW) browsing.

In the HSDPA system, channel state information (CSI) is made available to both the transmitter and the receiver, in order to realise a robust communication system structure. The HSDPA system is intended to increase the transmission rates and throughput, and to enhance the quality of service (QoS) experienced by different users. It transfers most of the functions from the base station controller (also known as the radio network controller or RNC) to the base transceiver station (node B).

The HSDPA system may also use a control technique referred to as an adaptive modulation and coding scheme (AMCS) to enable the base station to select different modulation and/or coding schemes under different channel conditions.

The signal transmission quality for a channel between the transmitter and a receiver (UE) varies significantly over time. Fig. 3 shows an example of the variation of a signal-to-interference ratio (SIR) a

downlink channel for four different users over a series of 5000 TTIs. This plot was obtained by a simulation. As illustrated, for a given UE the range of SIR values may be as much as from around +12dB to -15dB. The SIR value varies due to shadowing, Rayleigh fading, and change in distribution of the mobile UEs, as well as cellular area specifications including the propagation parameters and speeds of UEs.

Fig. 4 is a graph illustrating a relationship between a data transmission rate (throughput) and signal-to-interference ratio for four different modulation and coding combinations, also referred to as modulation-and-coding scheme (MCS) levels. The first three levels (MCS8, MCS6 and MCS5) are all quadrature amplitude modulation (QAM) schemes which differ from one another in the number (64 or 16) of constellation points used. The fourth level (MCS1) uses quadrature phase shift keying (QPSK) as its modulation scheme.

Each level uses coding defined by a coding parameter which, in this example, is expressed as a redundancy rate  $R$ . For the first two levels MCS8 and MCS6 the redundancy rate  $R$  is  $3/4$ , and for the third and fourth levels MCS5 and MCS1 the redundancy rate is  $1/2$ .

As can be seen from Figure 4, for SIR values lower than around -4dB MCS1 (QPSK,  $R=1/2$ ) is the best available option. The characteristic of this level is plotted with circles in the figure.

For SIR values in the range from around -4dB to around +2dB, MCS5 (16QAM,  $R=1/2$ ) provides the best transmission rate. The characteristic for this MCS level is illustrated by crosses in the figure.

For SIR values between around +2dB and +8dB MCS6 (16 QAM,  $R=3/4$ ) provides the best transmission rate. The characteristic for this MCS level is illustrated by diamond points in the figure.

Finally, for SIR values greater than around +8dB, MCS8 (64 QAM, R=3/4) provides the best transmission rate. The characteristic of this combination is illustrated by square points in the figure.

5 In the HSDPA system a technique such as adaptive modulation and coding (AMC) is used to adapt the MCS level in accordance with the variations of the channel condition (e.g. SIR value). Each UE produces a measure of the SIR of a downlink channel from the base station, and reports this measure (SIR value) to the base station. The base station then employs the reported SIR values for each UE, as well as information relating to the system limitations and available MCS levels, to identify the most efficient MCS level for the particular UE. Thus, UEs that have better channels or are located in the vicinity of the base station can employ higher levels of MCS and therefore enjoy higher transmission rates. The selection can be carried out, for example, by imposing thresholds (e.g. Th01, Th02 and Th03, as shown in Fig. 4) for moving to the next MCS level. Effectively, the result is a classification of the transmission rates based on the channel quality of each UE.

Ideally, each UE reports a SIR value in every TTI and the base station is capable of setting a new MCS level for each available channel in every TTI.

The HSDPA system may also employ a hybrid automatic repeat request (H-ARQ) technique.

Fig. 5 is a schematic diagram for use in explaining how the H-ARQ technique works. In this example, the technique is a so-called stop-and-wait (SAW) version of the technique. The figure shows packet transmissions in a single downlink channel HSPDSCH1 over a series of successive TTIs, TTI1 to TTI9. In TTI2 a first packet is transmitted to UE1. Upon receiving a packet, each UE checks whether the

transmission was error-free. If so, the UE sends an acknowledge message ACK back to the base station using an uplink control channel such as the dedicated physical control channel (DPCCH). If there was an  
 5 error in the transmission of the received packet, the UE sends a non-acknowledge message NACK back to the base station using the uplink channel.

In the example shown in Fig. 5, the first packet transmitted to UE1 in TTI2 fails to be received error-free, and accordingly some time later, in TTI4, UE1  
 10 sends the NACK message to the base station. In the HARQ technique it is permitted for the next packet destined for a particular UE to be transmitted without waiting for the acknowledge or non-acknowledge message of a packet previously transmitted to the same UE.  
 15 Thus, none of the transmission timeslots can go idle in the case of error-free channels, which gives the ability to schedule UEs freely. System capacity is saved while the overall performance of the system in terms of delivered data is improved.  
 20

For example, as shown in Fig. 5, before the NACK message for the first packet of UE1 is received by the base station, the base station transmits a second packet to UE1 in TTI4. Thus, this second packet for  
 25 UE1 is transmitted before the first packet for UE1 is retransmitted in TTI7 in response to the NACK message for the first transmission of the first packet.

In the HARQ technique, an erroneously-received packet (failed packet) is subject to a so-called chase combining process. In this process a failed packet is  
 30 resent by the transmitter and subsequently the receiver "soft" combines (for example using maximal ratio combining) all received copies of the same packet. The final SIR is determined as the sum of the respective  
 35 SIRs of the two packets being combined. Thus, the

chase combining process improves the SIR of the transmitted packets.

Further information regarding AMC and HARQ techniques may be found in 3GPP TR 25.848 V 4.0.0

5 (2001-03), Third Generation Partnership Project;

~~Technical Specification Group Radio Access Network;~~  
Physical Layer Aspects of UTRA High Speed Downlink Packet Access (release 4), March 2001, the entire content of which is incorporated herein by reference.

10 The switching between different MCS levels has been recognised as a very critical task, and recently there have been various proposals for optimising this switching. For example, in TSG R1-1-0589, TSG-RAN Working Group 1 meeting no. 20, Busan, Korea, May 21 to  
15 25 2001, NEC and Telecom MODUS jointly proposed an AMCS technique in which the thresholds for switching between different MCS levels are adjusted based on the ACK/NACK signalling from the UE. If NACK is signalled, the base station increases the thresholds by an upward amount  
20 S1. If ACK is signalled, the base station decreases the thresholds by a downward amount S2. The adjustments to the thresholds are limited and, for simplicity, the differences between thresholds may be fixed. The ratio between the upward amount S1 and the  
25 downward amount S2 may be determined based on the target error rate.

This AMCS method adjusts the thresholds between MCS levels to try to take into account different operating conditions in the wireless communication  
30 system. In particular, the optimum MCS levels under any particular signal conditions depend on the Doppler frequency (i.e. the speed at which the UE is moving) and the multi-path propagation conditions. For example, Fig. 6 shows the effect of the UE speed on the  
35 throughput-vs.-SIR characteristic for each of the different MCS levels in Fig. 4. Three lines are

plotted per MCS level: the highest line corresponds to a low UE speed of 3 km/h (Doppler frequency  $F_d=5.555\text{Hz}$ ), the middle line corresponds to a medium UE speed of 60 km/h ( $F_d=111.112\text{Hz}$ ), and the lowest line

5 corresponds to a high UE speed of 120 km/h ( $F_d=222.224\text{Hz}$ ). Fig. 6 shows that throughput declines as UE speed increases. It can also be seen that the optimum thresholds for switching between MCS levels are also changed as the UE speed changes.

10 Fig. 6 relates to a single-path Rayleigh fading mode. Fig. 7 shows the effect of different UE speeds under path conditions of two equal-gain paths. It can be seen that the characteristics are very different from Fig. 6, and it is clear that the optimum

15 thresholds are changed as the path conditions change.

The method proposed by NEC/Telecom MODUS changes the thresholds as the operating conditions change but the method does not provide a satisfactory solution as it increases or decreases the threshold each time an

20 ACK or NACK message is received, i.e. every frame. This appears to result in relatively poor performance at lower MCS levels for path conditions in which there is effectively a single dominant path, for example in open countryside.

25 According to a first aspect of the present invention there is provided an adaptive modulation and coding method comprising: selecting one of a plurality of different available modulation and coding levels to apply to a signal transmitted from a transmitter to a

30 receiver, the selection being based on a comparison between a signal transmission quality and a threshold value; and adjusting said threshold value when the signal transmission quality is within a predetermined range of said threshold value, and maintaining the

35 threshold value unchanged when the signal transmission quality is outside that range.

In such an AMCS method the threshold values are adjusted to take account of the prevailing signal transmission conditions but to a more limited extent than in previous proposals. This leads to improved  
5 throughput performance, especially under path conditions involving a single dominant path.

The signal transmission quality may be a signal-to-interference ratio, and may be measured by the receiver. The signal transmission quality may be  
10 measured based on the actual signal to which AMCS is being applied or on another signal, such as a pilot signal.

In the adjusting step the threshold value may be increased by an upward amount when the signal is not  
15 received successfully by said receiver, and may be decreased by a downward amount when the signal is received successfully by the receiver. In most communication systems the receiver is required to monitor whether the signal is received successfully, so  
20 using this information to help adjust the threshold value does not require any new information to be generated.

For example, in a system in which a cyclic redundancy check (CRC) is carried out on the received  
25 signal by the receiver in the adjusting step the threshold value may be increased by an upward amount when the received signal fails the cyclic redundancy check, and may be decreased by a downward amount when the received signal passes the cyclic redundancy check.  
30 Again, in such a system in which this information is already being generated, the AMCS method can use this information for the purpose of adjusting the threshold value without increasing the information-generating burden on the system.

35 The upward amount may be different from the downward amount. In a correctly-operating system,



preferably the downward amount is smaller than the upward amount. In a correctly-operating system, the received signal should be received successfully (e.g. pass the CRC) more frequently than it is received unsuccessfully (e.g. fail the CRC). Accordingly, to achieve stable adjustment or stability in the system, the downward amount, which is expected to be applied more often than the upward amount, should be smaller than the upward amount. If the signal transmission conditions are expected to be poor, on the other hand, the downward amount could be set higher than the upward amount.

For example, a ratio of the downward amount to the upward amount may be dependent upon a target error rate of the received signal. This target error rate is a measure of the expected success in receiving the signal. In one embodiment, the ratio of the downward amount to the upward amount is made equal to the ratio of the number of times the signal is received unsuccessfully to the number of times the signal is received successfully, i.e. the target error rate divided by 1 minus that error rate. In this way, the lower the target error rate the lower the ratio between the downward amount and the upward amount.

In one embodiment the downward amount and/or said upward amount is/are dependent upon a difference between said threshold value and said signal transmission quality. For example, the or each amount increases as the difference decreases. This has the effect of magnifying the adjustment amounts near to the threshold value, whilst limiting any adjustments further away from the threshold value.

In a practical system there may be more than two different available levels, in which case there is a threshold value for each pair of adjacent levels. In this case, preferably, each said threshold value is

adjusted only when said signal transmission quality is within a predetermined range of the threshold value concerned.

In this case, the predetermined range for at least one threshold value may be different from the predetermined range for another said threshold value.

This may be desirable as different levels have quite different characteristics, at least under some channel conditions. Having the ability to set different predetermined ranges for different thresholds can enable these differences to be taken into account.

The predetermined range may be set by a single value  $\alpha$  so that it extends from the threshold value minus  $\alpha$  to the threshold value plus  $\alpha$ . Alternatively, the range may be set by two different values  $\alpha_1$  and  $\alpha_2$  so that it extends from the threshold value minus  $\alpha_1$  to the threshold value plus  $\alpha_2$ . Again, having the ability to set different values  $\alpha_1$  and  $\alpha_2$  for the predetermined range can enable the different characteristics of MCS levels to be taken into account.

In one embodiment the adjusting step and the selecting step are carried out in the receiver, and the receiver reports the selected level to the transmitter.

In another embodiment the receiver reports the signal transmission quality to the transmitter, and the adjusting step and selecting step are carried out in the transmitter.

The selecting step may be carried out after the adjusting step so that the selection is based on the threshold values after any adjustments have been applied. Alternatively, the selecting step may be carried out before the adjusting step.

In the selecting step, it may also be desirable to make the selection dependent on whether or not the signal was received successfully. For example, if the signal was not received successfully, a move to a

higher level may be prevented, even if the signal transmission quality is now greater than the adjusted threshold value.

The method may be used in any communication system  
5 having a transmitter and a receiver in which an AMCS  
method is applicable. In particular the method may be  
used in a cellular wireless communication system, in  
which case the transmitter may be a base station of the  
wireless communication system, and the receiver may be  
10 a user equipment of the system.

The method is particularly useful in an HSDPA  
system, in which case the signal to which AMCS is  
applied is a downlink packet access signal.

According to a second aspect of the present  
15 invention there is provided adaptive modulation and  
coding apparatus comprising: level selecting means for  
selecting one of a plurality of different available  
modulation and coding levels to apply to a signal  
transmitted from a transmitter to a receiver, the  
20 selection being based upon a comparison between a  
signal transmission quality and a threshold value; and  
threshold value adjusting means operable, when the  
signal transmission quality is within a predetermined  
range of the threshold value, to adjust the threshold  
25 value, and also operable when the signal transmission  
quality is outside that range, to maintain the  
threshold value unchanged.

According to a third aspect of the present  
invention there is provided a user equipment, for use  
30 in a wireless communication system, comprising: level  
selecting means for selecting one of a plurality of  
different available modulation and coding levels to be  
applied by a base station of said system to a downlink  
signal transmitted from the base station to said user  
35 equipment, the selection being based on a comparison  
between a signal transmission quality and a threshold

value; threshold value adjusting means operable, when said signal transmission quality is within a predetermined range of said threshold value, to adjust said threshold value, and also operable, when said  
5 signal transmission quality is outside that range, to  
~~maintain said threshold value unchanged; and reporting~~  
means for reporting said selected level to said base station.

According to a fourth aspect of the present  
10 invention there is provided a base station, for use in a wireless communication system, comprising: report receiving means for receiving from a user equipment of said system a report of a downlink signal transmission quality produced by the user equipment; level selecting  
15 means for selecting one of a plurality of different available modulation and coding levels to apply to a downlink signal transmitted from the base station to the user equipment, the selection being based upon a comparison between the reported downlink signal  
20 transmission quality and a threshold value; and threshold value adjusting means operable, when the signal transmission quality is within a predetermined range of the threshold value, to adjust the threshold value, and also operable, when the signal transmission  
25 quality is outside that range, to maintain the threshold value unchanged.

In practice an AMCS method embodying the invention is likely to be implemented at least in part by a processor in the user equipment or in the base station  
30 which runs an operating program. Thus, according to a fifth aspect of the present invention there is provided an operating program which, when run on a processor in a user equipment of a wireless communication system, causes the user equipment to carry out the steps of:  
35 selecting one of a plurality of different available modulation and coding levels to be applied by a base

station of said system to a downlink signal transmitted from the base station to said user equipment, the selection being based on a comparison between a signal transmission quality and a threshold value; when said  
5 signal transmission quality is within a predetermined range of said threshold value, adjusting said threshold value, and, when said signal transmission quality is outside that range, and maintaining said threshold value unchanged; and reporting said selected level to  
10 said base station.

Similarly, according to a sixth aspect of the present invention there is provided an operating program which, when run on a processor in a base station of a wireless communication system, causes the  
15 base station to carry out the steps of: receiving from a user equipment of said system a report of a downlink signal transmission quality produced by the user equipment; selecting one of a plurality of different available modulation and coding levels to be applied by  
20 the base station to a downlink signal transmitted from the base station to said user equipment, the selection being based on a comparison between the reported downlink signal transmission quality and a threshold value; and when said signal transmission quality is  
25 within a predetermined range of said threshold value, adjusting said threshold value, and when said signal transmission quality is outside that range, maintaining said threshold value unchanged.

Further aspects of the present invention can  
30 provide control circuitry for use in a user equipment or base station and having means for carrying out the steps of the fifth and sixth aspects.

Reference will now be made, by way of example, to the accompanying drawings, in which:

Fig. 1, discussed hereinbefore, shows parts of a wireless communication system employing a HSDPA technique for downlink transmissions;

Fig. 2 shows an example of the operation of the HSDPA technique in the Fig. 1 system;

~~Fig. 3 is a graph illustrating an example variation~~  
in signal-to-interference ratio of a downlink channel over a series of transmission time intervals for four different UEs in a wireless communication system;

Fig. 4 is a graph for use in explaining an adaptive modulation and coding technique;

Fig. 5 is a schematic diagram for use in explaining an automatic repeat request process;

Fig. 6 is a graph corresponding to Fig. 4 for illustrating how a UE speed affects operation of an adaptive modulation and coding technique;

Fig. 7 is another graph for illustrating how different path conditions affect the operation of an adaptive modulation and coding technique;

Fig. 8 is a flowchart for use in explaining an AMCS method according to a first embodiment of the present invention;

Fig. 9 is a schematic view of parts of a wireless communication system for explaining signalling used therein;

Figs. 10 to 13 are graphs for comparing operation of an AMC method embodying the present invention with conventional methods under different UE speed and path conditions;

Fig. 14 is a schematic diagram for use in explaining a modification to the Fig. 8 method;

Figs. 15(A) and 15(B) are schematic diagrams for use in explaining how to set an upward amount used in the Fig. 8 method;

Fig. 16 is a flowchart for use in explaining an AMCS method according to a second embodiment of the present invention;

Fig. 17 presents a table giving detailed parameters of different MCS levels; and

Fig. 18 presents I-Q diagrams showing constellation points for example MCS levels.

Fig. 8 is a flowchart for use in explaining an AMCS method according to a first embodiment of the present invention. In this embodiment, the UE selects the appropriate MCS level for each frame of the downlink signal and reports the selected level to the base station.

In this example, the method is used to adapt the MCS level of a downlink packet access signal in an HSDPA system.

Fig. 9 is a schematic view for explaining signalling in the first embodiment.

For downlink signalling, four channels are used. A common pilot channel (CPICH) is used to broadcast a signal to all UEs in the cell served by the base station, in order to enable each UE to measure a downlink channel quality based on the CPICH signal. A high-speed downlink shared channel HS-DSCH is used to transmit packet data to a UE. A high-speed shared control channel HS-SCCH is used to carry transport format and resource related information (TFIR). This TFIR is, for example, 8 bits and includes information regarding a channelisation code, a MCS level, and a transport block size. The HS-SCCH also carries HARQ related information. This HARQ information is, for example, 12 bits and includes a HARQ process number, a redundancy version, a new data indicator, and a UE ID. A dedicated physical channel DPCH is optionally employed to transmit a high-speed data control signal

for indicating whether or not the high-speed packet mode is in use.

Uplink signalling is carried out using a high-speed dedicated physical control channel HS-DPCCH. This  
 5 channel is used to transmit a channel quality indicator, an HARQ acknowledgement (ACK/NACK) and, in the present embodiment, a MCS level selected by the UE.

Referring back to Fig. 8, the AMCS method according to the first embodiment operates on a frame-by-frame  
 10 basis. In each downlink frame (TTI) the method involves the steps S1 to S7.

In step S1, the UE produces a measure of downlink channel quality. This measure is, for example, based on the CPICH and represents a ratio of a received power  
 15  $\hat{I}_{or}$  of the CPICH signal to background noise including interference  $I_{oc}$ . The ratio  $\hat{I}_{or}/I_{oc}$  is a signal-to-interference ratio.

Also in step S1 the UE carries out a cyclic redundancy check (CRC) on the current frame of the HS-  
 20 DSCH signal. The CRC result (pass or fail) is needed to generate the ACK/NACK message but, as described below, is also used for another purpose in the present embodiment.

In step S2 the measure of downlink channel quality produced in step S1 is compared with a set of threshold values held by the UE for MCS selection purposes. There is one such threshold value for each pair of adjacent MCS levels. These threshold values correspond to the threshold values Th01, Th02 and Th03 described  
 30 with reference to Fig. 4 above. Based on the comparison, it is determined whether or not the measure of downlink channel quality is within a predetermined range  $\pm\alpha$ dB of one of the threshold values. As described later in more detail,  $\alpha$  may be different for  
 35 different threshold values in the set. Also, for each threshold value there may be two  $\alpha$ -values,  $\alpha_1$  and  $\alpha_2$ ,



and the downlink channel quality measure is considered to be within the predetermined range if it is greater than the threshold value less  $\alpha_1$  and less than the threshold value plus  $\alpha_2$ .

5        If the downlink channel quality measure is outside the predetermined range of each of the threshold values, it is determined in step S3 that no change to any of the threshold values is required, and processing proceeds to step S7. In step S7, the downlink channel  
 10        quality measure is compared with the different threshold values and the appropriate MCS level is selected based on the comparison. Thus, in the example of Fig. 4, if the downlink channel quality measure is greater than the threshold value Th03, MCS8 is  
 15        selected; if the measure is between the threshold values Th02 and Th03 MCS6 is selected; if the measure is between the threshold values Th01 and Th02, MCS5 is selected, and if the measure is less than the threshold value Th01, MCS1 is selected. The selected MCS level  
 20        is reported to the base station using the HS-DPCCH.

      If in step S2 the downlink channel quality measure is found to be within the predetermined range of one of the threshold values of the set, processing proceeds to step S4. In step S4 it is determined whether the CRC  
 25        result in step S1 was a pass or fail. If the result was a pass, i.e. the ACK message was sent from the UE back to the base station, the threshold value that has found to be within the predetermined range is decreased by a downward amount  $\Delta_{\text{Down}}$  in step S5. If, on the  
 30        other hand, the CRC result was a fail, i.e. the NACK message was sent by the UE back to the base station, the threshold value found to be within the predetermined range is increased by an upward amount  $\Delta_{\text{Up}}$  in step S6.

35        In steps S5 and S6 only the threshold value found to be within the predetermined range of the downlink

channel quality message is changed. Each of the remaining threshold values is left unchanged.

The upward and downward amounts  $\Delta Up$  and  $\Delta Down$  are discussed in detail below.

5        After step S5 or step S6, processing proceeds to step S7 to select the appropriate MCS level for the next downlink frame. In this case, therefore, the selection is made based on the updated set of threshold values.

10        Thus, in the first embodiment the threshold values are adjusted according to whether the downlink signal was received successfully by the UE or not (steps S4 to S6) as in the previous joint proposal of NEC and MODUS Telecom described in the introduction. However,  
15        whereas that previous proposal changed the threshold values every frame irrespective of downlink channel quality, the present embodiment only adjusts a threshold value if the downlink channel quality measure is within a predetermined range of that value.  
20        Otherwise, no change is made to the threshold values (step S3). This has the effect of limiting the changes to the threshold values in use of the method. Surprisingly, it is found that this simple measure provides a significant improvement in performance of  
25        the AMCS method, as will now be explained with reference to Figs. 10 to 13.

Fig. 10 shows a throughput versus downlink channel quality characteristic for a first conventional AMCS method having fixed threshold values (solid line), a  
30        second conventional AMCS method according to the joint NEC/MODUS Telecom proposal having adjustable threshold values (dotted line), and an AMCS method embodying the present invention (dashed line). Fig. 10 assumes that the UE is moving at a low speed of 3kph and that the  
35        channel estimation carried out by the UE is perfect.

Further it is assumed that the path conditions prevailing between the base station and the UE are such that there is a single dominant path. This kind of path condition arises, for example, in open countryside, as opposed to urban environments. As is evident from Fig. 10, an AMCS method embodying the present invention provides a significant improvement in performance over both conventional methods, over a very wide range of downlink channel qualities (e.g. from -6dB to +16dB). By contrast, the second conventional method has a significant dip in performance under the single path condition for downlink channel qualities in the range from about -10dB to +4dB. This dip is thought to arise from a bunching of the threshold values under the single dominant path condition.

Fig. 11 shows the corresponding results for the three methods, again under single path conditions, but with the UE moving at a medium speed of 60kph. In this case, also, it is evident that the AMCS method embodying the present invention avoids the undesirable dip in the second conventional method.

Fig. 12 shows some results obtained under two-equal-gain path conditions for the three different methods, and also shows (for comparison purposes) the performance of the first conventional method and a method embodying the present invention for single-path conditions. In Fig. 12, the UE is assumed to be moving at 3kph as in Fig. 10.

It can be seen that under two-equal-gain path conditions, a method embodying the present invention outperforms the two conventional methods, as well.

Finally, Fig. 13 shows results corresponding to Fig. 12 but for a UE moving at a very high speed of 120kph. Under these conditions as well, a method embodying the present invention outperforms both the conventional methods, in particular the first

conventional method (fixed thresholds) which has a significant performance dip for downlink channel qualities between +4 and +24dB.

Next, a possible modification of the first  
 5 embodiment will be described with reference to Fig. 14.  
 This modification relates to the operations carried out  
 in step S7 in Fig. 8. In this modification, as well as  
 making the selection of the MCS level for the next  
 downlink frame based on the updated set of threshold  
 10 values, the UE also takes account of the CRC result in  
 deciding the MCS level.

Fig. 14 shows the threshold value Th02 used for  
 selecting between MCS5 and MCS6, and the threshold  
 value Th03 used for selecting between MCS6 and MCS8.  
 15 Assume that the threshold values have been adjusted as  
 necessary in step S5 or S6 or maintained unchanged in  
 step S3 and that the current MCS level is MCS6.

Of course, if the downlink channel quality measure  
 is within a region R1, i.e. between Th02 and Th03, the  
 20 MCS level is maintained unchanged in step S7.  
 Similarly, if the downlink channel quality measure is  
 within a region R2, i.e. between Th02 and a lower  
 threshold value not shown in Fig. 14, the MCS level is  
 reduced from its current level MCS6 to a lower level  
 25 MCS5.

If, however, the downlink channel quality measure  
 is within a region R3, i.e. greater than Th03, the MCS  
 level is not automatically increased to MCS8 as in step  
 S7 as previously described. Instead, the MCS level is  
 30 maintained at its current level MCS6 when the CRC  
 result is a failure, and only increased to MCS8 when  
 the CRC result is a pass. In this way, selection of a  
 higher MCS level, although suggested by the threshold  
 value comparison, is prevented if the signal is not  
 35 received successfully.

As indicated above, the value  $\alpha$  (or pair of values  $\alpha_1$  and  $\alpha_2$ ) can be different for each threshold value. A typical value of  $\alpha$  is 1dB. However, for some threshold values, it may be appropriate to make  $\alpha$  large, or at least to make one of  $\alpha_1$  and  $\alpha_2$  large in relation to the other. For example, Fig. 7, discussed in the introduction, showed that when the path conditions are two equal-gain paths, and the fading model is a Rayleigh fading model, MCS6 always achieves a greater throughput than MCS8. In other words, the threshold value Th03 for selecting between MCS6 and MCS8 is redundant, which is equivalent to it having an infinite value. This suggests that Th03 can vary in a very wide range. In this case  $\alpha_2$  for Th03 can be chosen to be arbitrarily large or even infinite.

The upward amount  $\Delta Up$  and downward amount  $\Delta Down$  are preferably set such that

$$\Delta Down = \Delta Up \frac{FER}{1 - FER}, \quad \dots (1)$$

where  $FER$  is a target frame error rate.

The target frame error rate may be different for each different threshold value. A FER value of around 10 to 15% may be considered typical. The target FER could alternatively be a target FER value for the currently-selected MCS level, for example a target value for a quality measure in the middle of the band of quality measures over which that MCS level is selected.

It is also possible to make one or both of the upward amount  $\Delta Up$  and the downward amount  $\Delta Down$  dependent upon a difference between the present downlink channel quality measure and the threshold value being adjusted. For example,

$$\Delta Up = \frac{\Delta Up_0}{\text{Max}\{a, b(|SIR - Thx|)\}} \quad \dots (2)$$

where  $\Delta Up_0$  is an initial value of  $\Delta Up$ ,  $Thx$  is the threshold value being adjusted,  $SIR$  is the present downlink channel quality measure, and  $a$  and  $b$  are constants. Here  $a > 0$  (a sensible value could be 0.25 to 1) and  $b \geq 0$ .

This leads to a relationship between  $\Delta Up$  and a difference between  $SIR$  and  $Thx$  as shown in Fig. 15(A). The constant  $b$  controls the slope of the side portions in Fig. 15(A), and the constant  $a$  controls the level at which  $\Delta Up$  is capped. The relationship between  $\Delta Up$  and  $\Delta Down$  may be the same as in equation (1) above.

Alternatively,

$$\Delta Up = (\Delta Up_0) * \max\{0, \beta - b(|SIR - Thx|)\} \quad \dots (3)$$

where  $\beta$  and  $b$  are constants and  $b \geq 0$ . The constant  $\beta$  represents a threshold adjustment bandwidth similar to  $\alpha$ , and it is possible to set  $\beta = \alpha$ . Equation (3) results in a relationship between  $\Delta Up$  and the difference between  $SIR$  and  $Thx$  as shown in Fig. 15(B). Equation (1) may be used to set  $\Delta Down$  in this case also.

Equations (2) and (3) have the effect of increasing  $\Delta Up$  (and  $\Delta Down$ ) when the downlink channel quality measure becomes closer to one of the current threshold values.

In the first embodiment described with reference to Fig. 8, the adjustment of the threshold values and the selection of the MCS level was made in the UE. However, it is not necessary for these operations to be carried out in the UE. It is also possible for one or both of these operations to be carried out in the base station, as will now be described in relation to a second embodiment of the present invention.

Referring to Fig. 16, in a first step S10 the UE produces a measure of downlink channel quality and also carries out a cyclic redundancy check on the current

frame of the HS-DSCH. The downlink signal quality measure and the CRC result are reported by the UE to the base station via the HS-DPCCH. The base station then carries out steps S11 to S15, which correspond  
 5 respectively to the steps S2 to S6 in Fig. 6, except  
 that the operations are in this case carried out in the  
 base station rather than in the UE.

In step S16 the base station selects the MCS<sup>†</sup> level for the next downlink frame based on the threshold  
 10 values (in the same way as the UE did in step S7 in Fig. 8).

In both the first and second embodiments the MCS selection made according to the downlink channel quality measure (step S7 or S16) may be overridden by  
 15 the base station, for example depending on the amount of data waiting at the base station for transmission to the UE concerned.

Although in the examples described above the available MCS levels were MCS1, MCS5, MCS6 and MCS8, it  
 20 will be appreciated that any two or more different MCS levels may be made available in embodiments of the present invention. A table showing the characteristics of MCS levels 1 to 8 as an example is presented in Figure 17.

25 As is well known in the art, different modulation schemes involve different numbers of bits per modulated symbol. Quadrature phase shift keying (QPSK) has 2 bits per symbol, 8 phase shift keying (8PSK) has 3 bits per symbol, 16 quadrature amplitude amplitude  
 30 modulation (16QAM) has 4 bits per symbol, and 64 quadrature amplitude amplitude modulation (64QAM) has 6 bits per symbol. Each scheme results in  $2^n$  constellation points, where n is the number of bits per symbol. The constellation points in I-Q signal space  
 35 are shown for 8PSK, 16QAM and 64QAM in Figure 18.

Although an example of the present invention has been described above in relation to a wideband CDMA

network having an asynchronous packet mode, it will be appreciated that the present invention can also be applied to any other networks in which AMCS can be used. These networks could be, or could be adapted from, other CDMA networks such as an IS95 network.

These networks could also be, or be adapted from other mobile communication networks not using CDMA, for example networks using one or more of the following multiple-access techniques: time-division multiple access (TDMA), wavelength-division multiple access (WDMA), frequency-division multiple access (FDMA) and space-division multiple access (SDMA).

Those skilled in the art will appreciate that a microprocessor or digital signal processor (DSP) may be used in practice to implement some or all of the functions of the base station and/or user equipment in embodiments of the present invention.



**CLAIMS:**

1. An adaptive modulation and coding method comprising:

selecting one of a plurality of different  
5 available modulation and coding levels to apply to a  
signal transmitted from a transmitter to a receiver,  
the selection being based on a comparison between a  
signal transmission quality and a threshold value; and  
adjusting said threshold value when the signal  
10 transmission quality is within a predetermined range of  
said threshold value, and maintaining the threshold  
value unchanged when the signal transmission quality is  
outside that range.

2. A method as claimed in claim 1, wherein said  
15 signal transmission quality is a signal-to-interference  
ratio.

3. A method as claimed in claim 1 or 2, wherein  
said signal transmission quality is measured by the  
receiver.

20 4. A method as claimed in any preceding claim,  
wherein in said adjusting step said threshold value is  
increased by an upward amount when said signal is not  
received successfully by said receiver, and is  
decreased by a downward amount when the signal is  
25 received successfully by the receiver.

5. A method as claimed in any one of claims 1 to  
4, wherein in said adjusting step said threshold value  
is increased by an upward amount when the signal  
received by the receiver fails a cyclic redundancy  
30 check, and is decreased by a downward amount when the  
received signal passes the cyclic redundancy check.

6. A method as claimed in claim 4 or 5, wherein  
said upward amount is different from said downward  
amount.

35 7. A method as claimed in claim 6, wherein said  
downward amount is smaller than said upward amount.

8. A method as claimed in any one of claims 4 to 7, wherein a ratio of said downward amount to said upward amount is dependent upon a target error rate of the received signal.

5 9. A method as claimed in any one of claims 4 to 8, wherein said downward amount and/or said upward amount is/are dependent upon a difference between said threshold value and said signal transmission quality.

10 10. A method as claimed in claim 9, wherein the or each said amount increases as said difference decreases.

11. A method as claimed in any preceding claim, having a threshold value for each pair of adjacent said levels, and in said selecting step the selection is  
15 based on a comparison between said signal transmission quality and the threshold values.

12. A method as claimed in claim 11, wherein each said threshold value is adjusted only when said signal transmission quality is within a predetermined range of  
20 the threshold value concerned.

13. A method as claimed in claim 11 or 12, wherein said predetermined range for at least one said threshold value is different from said predetermined range for another said threshold value.

25 14. A method as claimed in any preceding claim, wherein the adjusting step and the selecting step are carried out in said receiver, and the receiver reports the selected level to the transmitter.

15. A method as claimed in any one of claims 1 to 13, wherein the receiver reports said signal  
30 transmission quality to the transmitter, and the adjusting step and selecting step are carried out in the transmitter.

16. A method as claimed in any preceding claim,  
35 wherein said selecting step is carried out after said adjusting step, and in said selecting step selection of

a higher level, if indicated by said comparison between said signal transmission quality and said threshold value(s) as adjusted or maintained in said adjusting step, is prevented when the signal was not received successfully by the receiver.

17. ~~A method as claimed in any preceding claim,~~ wherein said transmitter is a base station of a wireless communication system, and the receiver is a user equipment of said system.

18. A method as claimed in claim 17, wherein said signal is a downlink packet access signal.

19. Adaptive modulation and coding apparatus comprising:

level selecting means for selecting one of a plurality of different available modulation and coding levels to apply to a signal transmitted from a transmitter to a receiver, the selection being based upon a comparison between a signal transmission quality and a threshold value; and

threshold value adjusting means operable, when the signal transmission quality is within a predetermined range of the threshold value, to adjust the threshold value, and also operable when the signal transmission quality is outside that range, to maintain the threshold value unchanged.

20. A user equipment, for use in a wireless communication system, comprising:

level selecting means for selecting one of a plurality of different available modulation and coding levels to be applied by a base station of said system to a downlink signal transmitted from the base station to said user equipment, the selection being based on a comparison between a signal transmission quality and a threshold value;

threshold value adjusting means operable, when said signal transmission quality is within a

predetermined range of said threshold value, to adjust said threshold value, and also operable, when said signal transmission quality is outside that range, to maintain said threshold value unchanged; and

5        reporting means for reporting said selected level to said base station.

21. A base station, for use in a wireless communication system, comprising:

report receiving means for receiving from a user  
10 equipment of said system a report of a downlink signal transmission quality produced by the user equipment;

level selecting means for selecting one of a plurality of different available modulation and coding levels to apply to a downlink signal transmitted from  
15 the base station to the user equipment, the selection being based upon a comparison between the reported downlink signal transmission quality and a threshold value; and

threshold value adjusting means operable, when the  
20 signal transmission quality is within a predetermined range of the threshold value, to adjust the threshold value, and also operable, when the signal transmission quality is outside that range, to maintain the threshold value unchanged.

22. An operating program which, when run on a processor in a user equipment of a wireless communication system, causes the user equipment to carry out the steps of:

selecting one of a plurality of different  
30 available modulation and coding levels to be applied by a base station of said system to a downlink signal transmitted from the base station to said user equipment, the selection being based on a comparison between a signal transmission quality and a threshold  
35 value;

when said signal transmission quality is within a predetermined range of said threshold value, adjusting said threshold value, and, when said signal transmission quality is outside that range, and  
5 maintaining said threshold value unchanged; and  
reporting said selected level to said base station.

23. An operating program which, when run on a processor in a base station of a wireless communication  
10 system, causes the base station to carry out the steps of:

receiving from a user equipment of said system a report of a downlink signal transmission quality produced by the user equipment;  
15 selecting one of a plurality of different available modulation and coding levels to be applied by the base station to a downlink signal transmitted from the base station to said user equipment, the selection being based on a comparison between the reported  
20 downlink signal transmission quality and a threshold value; and

when said signal transmission quality is within a predetermined range of said threshold value, adjusting said threshold value, and when said signal transmission  
25 quality is outside that range, maintaining said threshold value unchanged.

24. An adaptive modulation and coding method substantially as hereinbefore described with reference to Figs. 8 to 18 of the accompanying drawings.

30 25. Adaptive modulation and coding apparatus substantially as hereinbefore described with reference to Figs. 8 to 18 of the accompanying drawings.

26. A user equipment for use in a wireless communication system substantially as hereinbefore  
35 described with reference to Figs. 8 to 18 of the accompanying drawings.

27. A base station for use in a wireless communication system substantially as hereinbefore described with reference to Figs. 8 to 18 of the accompanying drawings.

5 28. An operating program for a processor in a user equipment or in a base station of a wireless communication system substantially as hereinbefore described with reference to Figs. 8 to 18 of the accompanying drawings.

10

ABSTRACT  
ADAPTIVE MODULATION AND CODING

An adaptive modulation and coding method comprises  
5 selecting (S7) one of a plurality of different  
available modulation and coding levels to apply to a  
signal transmitted from a transmitter to a receiver.  
The selection is based on a comparison between a signal  
transmission quality ( $\hat{I}_{or}/I_{oc}$ ) and one or more threshold  
10 values. The or each threshold value is adjusted (S5,  
S6) when the signal transmission quality is within a  
predetermined range of that threshold value, and is  
maintained unchanged (S3) when the signal transmission  
quality is outside that range.  
15 By maintaining the threshold value unchanged when  
the signal transmission quality is outside the range of  
that value the adjustments to the threshold value(s)  
are limited, whilst still enabling the threshold  
value(s) to take account of prevailing signal  
20 transmission conditions. This leads to improved  
throughput performance, especially under path  
conditions involving a single dominant path.

[Fig. 8]





1/18




FIGURE 1



	TT11	TT12	TT13	TT14	TT15	TT16	TT17	TT18	TT19
Node B1 Channel Code 1	UE50 Packet 1	UE11 Packet 1	UE3 Packet 1	UE23 Packet 1	UE4 Packet 2	UE6 Packet 1	UE1 Packet 1	UE23 Packet 1	UE7 Packet 1
Node B1 Channel Code 2	UE50 Packet 2	UE50 Packet 3	UE4 Packet 1	UE1 Packet 2	UE7 Packet 1	UE50 Packet 2	UE4 Packet 1	UE1 Packet 2	UE17 Packet 1
Node B1 Channel Code 3	UE11 Packet 1	UE50 Packet 4	UE1 Packet 1	UE4 Packet 2	UE23 Packet 2	UE2 Packet 8	UE11 Packet 4	UE15 Packet 1	UE23 Packet 2
Node B1 Channel Code 4	UE11 Packet 2	UE50 Packet 5	UE50 Packet 10	UE11 Packet 8	UE16 Packet 2	UE9 Packet 2	UE40 Packet 2	UE34 Packet 1	UE9 Packet 3
Node B1 Channel Code 5	UE11 Packet 3	UE2 Packet 5	UE16 Packet 1	UE9 Packet 1	UE11 Packet 3	UE24 Packet 2	UE43 Packet 2	UE16 Packet 1	UE11 Packet 10
Node B1 Channel Code 6	UE11 Packet 4	UE11 Packet 5	UE2 Packet 6	UE1 Packet 3	UE4 Packet 1	UE11 Packet 9	UE40 Packet 3	UE1 Packet 5	UE4 Packet 1
Node B1 Channel Code 7	UE2 Packet 1	UE50 Packet 6	UE50 Packet 11	UE3 Packet 2	UE24 Packet 1	UE2 Packet 8	UE38 Packet 1	UE38 Packet 5	UE50 Packet 14
Node B1 Channel Code 8	UE2 Packet 2	UE50 Packet 7	UE50 Packet 12	UE11 Packet 9	UE43 Packet 1	UE4 Packet 3	UE38 Packet 2	UE3 Packet 2	UE14 Packet 1
Node B1 Channel Code 9	UE2 Packet 3	UE50 Packet 8	UE11 Packet 6	UE40 Packet 1	UE50 Packet 13	UE3 Packet 1	UE38 Packet 3	UE40 Packet 1	UE43 Packet 2
Node B1 Channel Code 10	UE2 Packet 4	UE50 Packet 9	UE11 Packet 7	UE50 Packet 13	UE2 Packet 7	UE43 Packet 2	UE38 Packet 4	UE50 Packet 14	UE2 Packet 9



3/18




FIGURE 3






Figure 4








Figure 5






FIGURE 6






FIGURE 7






FIGURE 8





9/18




FIGURE 9



10/18




FIGURE 10






FIGURE 11



12/18





FIGURE 12







$\hat{I}_{or} / I_{oc}$

FIGURE 13



Current MCS Selection MCS = 6




Figure 14






FIGURE 15(A)




FIGURE 15(B)






FIGURE 16






IMCS Number	1	2	3	4	5	6	7	8
Modulation Scheme	QPSK	QPSK	8PSK	8PSK	16QAM	16QAM	64QAM	64QAM
Spreading Factor SF	16	16	16	16	16	16	16	16
Symbols/slot	160	160	160	160	160	160	160	160
Bits/slot	320	320	480	480	640	640	960	960
TTL (ms)	2	2	2	2	2	2	2	2
Number Of slots/frame	3	3	3	3	3	3	3	3
Bits/frame	960	960	1440	1440	1920	1920	2880	2880
TPC, TFCI and Pilot	0	0	0	0	0	0	0	0
Code Length RF	960	960	1440	1440	1920	1920	2880	2880
Padding	0	2	0	2	0	2	0	2
Code Length RM (Rate*DataLength + Tail bit)	960	968	1440	1438	1920	1918	2880	2878
Rate (selected rates)	Rate 1/2	Rate 3/4	Rate 1/2	Rate 3/4	Rate 1/2	Rate 3/4	Rate 1/2	Rate 3/4
Code Length (3*DataLength + 4*(k-1))	1443	2154	2163	3234	2883	4314	4323	6474
K <sub>c</sub> :1	3	3	3	3	3	3	3	3
Data Length	477	714	717	1074	957	1434	1437	2154
CRC Length	24	24	24	24	24	24	24	24
InfoData Length	453	690	693	1050	933	1410	1413	2130
InfoData Rate	226.5 Kbps	345 Kbps	346.5 Kbps	525 Kbps	466.5 Kbps	705 Kbps	706.5 Kbps	1065 Kbps
Number of Multicodes	10	10	10	10	10	10	10	10
Data Rate x Multicodes	2.265 Mbps	3.450 Mbps	3.465 Mbps	5.250 Mbps	4.665 Mbps	7.050 Mbps	7.065 Mbps	10.650 Mbps


Figure 17




8PSK



16 QAM



64 QAM



18/18

Figure 18

